

Data Sheet

VIAVI

MP-60 and MP-80

Miniature USB 2.0 Power Meters with FiberChekPRO™ Integration

Miniature USB Power Meter

The MP-series power meter is a miniature device that measures optical power via a USB 2.0 connection to a PC/laptop or VIAVI test mainframe. This unique device makes digital processing of optical power measurements possible and integrates directly with VIAVI Solutions FiberChekPRO software, the industry-leading automated fiber inspection and analysis program. Its size, functionality, and ease-of-use makes it an extremely useful and practical tool when testing optical power levels. The simple, straightforward, and intuitive software interface offers a well-organized digital solution for both fiber inspection and test procedures.



Key Benefits

- Quickly and easily test optical power on PC/laptop or VIAVI test mainframe
- Small form-factor design for ultimate portability
- Archives and creates custom logs for all results
- Integrate power measurement results into FiberChekPRO files and reports
- Easy and clear digital readouts

Key Features

- Lightweight, small form-factor design for ultimate portability
- Generates measurements in dB, mW, and dBm
- Compatible with FiberChekPRO fiber inspection and analysis software; integrated reporting capabilities within FiberChekPRO
- Simple, accurate, and instant push-button measurement results can be electronically archived, logged, and printed
- Dedicated for all single-mode and multimode applications including LAN, telecom, CATV, and DWDM testing
- Automated data-logging capabilities
- Automatic wavelength detection
- Measures optical power with multiple pre-calibrated wavelengths: MP-60 at 850/1300/1310/1490/1550 nm; MP-80 at 980/1310/1480/1550 nm



Components and Functions Power LED Dust cover USB plug Run button Patch-cord input

Specifications

MP-60		
Dimensions	86 x 25 x 19 mm (3.4 x 1.0 x 0.8 in)	
Weight	14 g (0.5 oz)	
USB type	USB 2.0	
Connector input	Universal 2.5 and 1.25 mm	
	connectors	
Measurement types	dB, mW, dBm	
Detector type	Germanium	
Power source	USB port on PC or laptop	
Display range	-65 to +10 dBm	
Max. permitted input level	+13 dBm	
Intrinsic uncertainty ¹	±0.20 dB (±5%)	
Linearity¹ (-50 to +5 dBm)	±0.06 dB	
Standard wavelength settings	850, 980, 1300, 1310, 1490, 1550, 1625	
	nm	
Wavelength range	780 to 1650 nm	
Wavelength and modulation	270 Hz, 330 Hz, 1 kHz, 2 kHz	
1300, 1310, 1490, 1550, 1625 nm	-50 to +10 dBm	
850, 980 nm	-45 to +10 dBm	
Warranty	1 yr	

MP-80		
Dimensions	86 x 25 x 19 mm (3.4 x 1.0 x 0.8 in)	
Weight	14 g (0.5 oz)	
USB type	USB 2.0	
Connector input	Universal 2.5 and 1.25 mm	
	connectors	
Measurement types	dB, mW, dBm	
Detector type	Germanium	
Power source	USB port on PC or laptop	
Display range	−50 to +26 dBm	
Max. permitted input level	+27 dBm	
Intrinsic uncertainty ¹	±0.20 dB (±5%)	
Linearity¹ (-32 to +20 dBm)	±0.06 dB	
Standard wavelength settings	850, 980, 1300, 1310, 1490, 1550, 1625	
	nm	
Wavelength range	780 to 1650 nm	
Wavelength and modulation	270 Hz, 330 Hz, 1 kHz, 2 kHz	
1300, 1310, 1490, 1550, 1625 nm	-35 to +23 dBm	
850, 980 nm	-30 to +23 dBm	
Warranty	1 yr	

^{1.} Under the following reference conditions: –20 dBm (CW), 1300 nm ±1 nm, 23°C ±3K, 45 to 75% relative humidity, 9 to 50 μ m fiber.Ordering Information

Ordering Information

Description	
USB Optical Power Meter: Includes software, 2.5mm interface , carrying pouch	
USB Optical Power Meter: Includes software, 2.5mm interface, 1.25 interface , 30" (75cm) USB extender, carrying pouch	
USB Optical Power Meter - High Power - Includes software, 2.5mm interface , carrying pouch	
USB Optical Power Meter - High Power - Includes software, 2.5mm interface, 1.25 interface , 30" (75cm) USB extender, carrying pouch	
Digital Inspection & Test Kit: Includes FBP-P5000i Digital Probe Microscope, inspection tips (SC, LC, Univ. 2.5 & 1.25 male), MP-60 USB Optical Power Meter with 2.5mm and 1.25 interfaces , software, 30" USB extender, carrying case	FIT-SD103
Digital Inspection & Test Kit: Includes FBP-P5000i Digital Probe Microscope, inspection tips (SC, LC, Univ. 2.5 & 1.25 male), MP-80 USB Optical Power Meter with 2.5mm and 1.25 interfaces , software, 30" USB extender, carrying case	FIT-SD113



